

White Tape Light

800LM - 2400K

Light efficiency:

n/a Lumen/Watt

Output: 777 lm/f

Light quality:

CRI: 94.9


Peak: 264 cd

Color temperature:

2386 K

Power: - W

PF: n/a





Beam angle


115.3°

White Tape Light


800LM - 2400K



TM30: 94.5



CRI: 94.9 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
93.4	95.6	97.9	92.3	92.6	90.7	97.5	98.9	97.5	92.8	87.0	86.2	93.1	97.2	96.0


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
96.7	96.4	93.5	95.8	95.7	92.4	94.0	92.9	94.7	96.1	95.0	92.4	91.0	90.8	96.1	91.8

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
93.0	92.6	93.1	93.8	91.1	88.1	88.4	91.8	94.0	94.3	94.5	94.6	94.5	90.0	93.2

CQS: 91.7



Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
2386 K	94.9	97.5	94.5	104.8	91.7	0.481	0.404	0.279	0.352	-0.0034

Rf 94.5

Rg 104.8

		Graphic shifts (%)	
Hue Bin	R_f	Chroma	Hue
1	97	0%	0%
2	96	1%	0%
3	94	2%	1%
4	96	1%	-1%
5	96	2%	2%
6	92	5%	2%
7	94	3%	-1%
8	93	4%	-2%
9	95	2%	-1%
10	96	2%	-1%
11	95	4%	0%
12	92	3%	-3%
13	91	4%	-8%
14	91	3%	-6%
15	96	0%	-2%
16	92	1%	-6%

