

Angolo

L5 - 3000K

Light efficiency:

n/a Lumen/Watt

Light quality:


CRI: 96.2

Color temperature:

2952 K


OPTIQUE

118.2°




Output: 558 Lumen Power consumption: -


Spectral distribution




Color coordinates



White color point




CRI R values



| Color temperature | Color rendering index | Red component | Color fidelity | Color gamut | Color quality scale | Color coordinate cie 1931 | Color coordinate cie 1931 | Color coordinate | Color coordinate | Color deviation from black body |
|-------------------|-----------------------|---------------|----------------|-------------|---------------------|---------------------------|---------------------------|------------------|------------------|---------------------------------|
| CCT | CRI | CRI R9 | TM30 Rf | TM30 Rg | CQS | x | y | u | v | Δuv |
| 2952 K | 96.2 | 93.9 | 94.7 | 104.1 | 94.8 | 0.435 | 0.394 | 0.254 | 0.345 | -0.0038 |

Beam details



Beam angles

| Beam angle 50% | Field angle 10% | Cutoff angle 2,5% |
|----------------|-----------------|-------------------|
| 118.2° | 184.6° | 210.9° |


Beam intensities

| Peak intensity | Int. ratio in 120° cone | Int. ratio in 90° cone |
|----------------|-------------------------|------------------------|
| 167 cd | 69.0% | 46.2% |

Beam intensities from 1-20m

| 1m | 2m | 3m | 4m | 5m | 6m | 7m | 8m | 9m | 10m | 11m | 12m | 13m | 14m | 15m | 16m | 17m | 18m | 19m | 20m |
|---------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 3.3ft | 6.6ft | 9.8ft | 13.1ft | 16.4ft | 19.7ft | 23ft | 26.2ft | 29.5ft | 32.8ft | 36.1ft | 39.4ft | 42.7ft | 45.9ft | 49.2ft | 52.5ft | 55.8ft | 59.1ft | 62.3ft | 65.6ft |
| 166lx | 42lx | 18lx | 10lx | 7lx | 5lx | 3lx | 3lx | 2lx | 2lx | 1lx | 1lx | 1lx | 1lx | 1lx | 1lx | 1lx | 1lx | 0lx | 0lx |
| 15.5fcd | 3.9fcd | 1.7fcd | 1fcd | 0.6fcd | 0.4fcd | 0.3fcd | 0.2fcd | 0.2fcd | 0.2fcd | 0.1fcd | 0.1fcd | 0.1fcd | 0.1fcd | 0.1fcd | 0.1fcd | 0.1fcd | 0fcd | 0fcd | 0fcd |

Power scope



| Power | Power factor | Power frequency |
|-------|--------------|-----------------|
| - W | n/a | {FREQ } Hz |

| Nominal voltage | Voltage | Current |
|-----------------|---------|---------|
| 230 V | 112 V | 0.000 A |



(844) 454-2910



solutions@optique-lighting.com



optique-lighting.com