

Angolo

L6 - 3000K

Light efficiency:

n/a Lumen/Watt

Light quality:


CRI: 96.2

Color temperature:

2901 K


OPTIQUE

118.3°




Output: 721 Lumen Power consumption: -


Spectral distribution




Color coordinates



White color point




CRI R values



| Color temperature | Color rendering index | Red component | Color fidelity | Color gamut | Color quality scale | Color coordinate cie 1931 | Color coordinate cie 1931 | Color coordinate | Color coordinate | Color deviation from black body |
|-------------------|-----------------------|---------------|----------------|-------------|---------------------|---------------------------|---------------------------|------------------|------------------|---------------------------------|
| CCT | CRI | CRI R9 | TM30 Rf | TM30 Rg | CQS | x | y | u | v | Δuv |
| 2901 K | 96.2 | 97.6 | 94.5 | 104.1 | 94.7 | 0.439 | 0.396 | 0.256 | 0.346 | -0.0036 |

Beam details



Beam angles

| Beam angle 50% | Field angle 10% | Cutoff angle 2,5% |
|----------------|-----------------|-------------------|
| 118.3° | 185.2° | 212.1° |


Beam intensities

| Peak intensity | Int. ratio in 120° cone | Int. ratio in 90° cone |
|----------------|-------------------------|------------------------|
| 215 cd | 68.8% | 46.1% |

Beam intensities from 1-20m

| 1m | 2m | 3m | 4m | 5m | 6m | 7m | 8m | 9m | 10m | 11m | 12m | 13m | 14m | 15m | 16m | 17m | 18m | 19m | 20m |
|---------|-------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 3.3ft | 6.6ft | 9.8ft | 13.1ft | 16.4ft | 19.7ft | 23ft | 26.2ft | 29.5ft | 32.8ft | 36.1ft | 39.4ft | 42.7ft | 45.9ft | 49.2ft | 52.5ft | 55.8ft | 59.1ft | 62.3ft | 65.6ft |
| 214lx | 54lx | 24lx | 13lx | 9lx | 6lx | 4lx | 3lx | 3lx | 2lx | 2lx | 1lx | 1lx | 1lx | 1lx | 1lx | 1lx | 1lx | 1lx | 1lx |
| 19.9fcd | 5fcd | 2.2fcd | 1.2fcd | 0.8fcd | 0.6fcd | 0.4fcd | 0.3fcd | 0.2fcd | 0.2fcd | 0.2fcd | 0.1fcd | 0.1fcd | 0.1fcd | 0.1fcd | 0.1fcd | 0.1fcd | 0.1fcd | 0.1fcd | 0fcd |

Power scope



| Power | Power factor | Power frequency |
|-------|--------------|-----------------|
| - W | n/a | {FREQ } Hz |

| Nominal voltage | Voltage | Current |
|-----------------|---------|---------|
| 230 V | 113 V | 0.000 A |



(844) 454-2910



solutions@optique-lighting.com



optique-lighting.com